E55/E55B

15" (13.8" VIEWABLE) E^{2®} SERIES CRT MONITOR

WITH ONVIEW[®] CONTROLS

Affordable performance.

ViewSonic's E55 and E55B 15" (13.8" viewable) CRT monitors deliver on the ViewSonic® tradition of quality and RELIABILITY AT AN AFFORDABLE PRICE. Flicker-free 1024x768 resolution reduces eyestrain for comfortable viewing of spreadsheets, word processing and Internet content. The fine 0.23mm horizontal dot pitch produces clear, CRISP IMAGES WITH PRECISE PICTURE DEFINITION. Antistatic, anti-glare screen reflects light while maintaining high-quality images. Adjust your screen with the OnView® controls and secure them with the OSD lock function to ensure optimum screen performance. The E55 and E55B are ideal for small and home offices and student or Internet users.

It's not just another affordable CRT. It's a ViewSonic.



QUALITY AND RELIABILITY FOR WORK OR HOME

- > 0.23mm horizontal dot pitch; 0.27mm diagonal dot pitch This fine dot pitch produces clear, crisp images with precise picture definition, even at the highest resolutions.
- > 1280x1024 maximum resolution Displays a maximum resolution of 1280x1024; 1024x768 at 87Hz flicker-free refresh rate for easy viewing.
- > OnView[®] controls including OSD lock function

All screen adjustments are made via an on-screen menu using simple controls. The new OSD lock feature prevents accidental changes to optimized monitor settings.

> Anti-static, anti-reflection screen

This anti-static, anti-reflection screen coating refracts unwanted light away from the user while maintaining the highest quality of the displayed image.

- > PC and Mac[®] compatible
- > MPR II and ENERGY STAR® certified

This monitor complies with the world's strictest standards of low radiation, safety, ergonomics, recycling and power management while saving costs through automatic power saving modes.

> Three year limited warranty 24/7 free technical support*.





Downloaded from www.Manualslib.com manuals search engine

E55/E55B 15" (13.8" VIEWABLE) E^{2®} SERIES CRT MONITOR WITH ONVIEW[®] CONTROLS







Available colors: Black (E55B), Beige (E55)

CRT	Туре	15" (13.8" viewable) 90° deflection
	Dot Pitch	0.23mm (horizontal) x 0.13mm (vertical); 0.27mm diagonal
	Phosphor	RGB medium-short persistence
	Glass Surface	Tint: TM~57%, anti-static, anti-reflection screen coating
VIDEO SIGNAL	Video	RGB Analog (75 ohms, 0.7/1.0Vp-p)
	Sync	H/V separated (TTL), composite
	Frequency	F _h : 30~70kHz, F _v : 50~160Hz
COMPATIBILITY	PC	IBM and compatibles (from VGA up to 1280x1024 non-interlaced
	Mac®**	Power Mac G3/G4/G5 (from 640x480 to 1024x768)
CONNECTOR	Analog	15-pin mini D-sub
	Power	3-pin plug (CEE22)
POWER	Voltage	AC 90–132V / 198–264VAC (auto switch), 50/60Hz (+/-3)
	Consumption	70W (typ)
CONTROLS	Basic	power, 1, left, right, 2
	OnView®	Contrast, brightness, degauss, H. size, H. position, V. size,
		V. position, pincushion, trapezoid, pinbalance, parallelogram,
		tilt , moiré, ViewMatch® color (9300K, 6500K), recall, ViewMeter®
		OSD position, language, zoom
VIDEO INPUT	Bandwidth	118MHz
MISCONVERGENCE		0.25mm (max) at center
		0.35mm (max) at corner
DISPLAY AREA	Factory Setting	270mm x 202mm
(HORZ. x VERT.)	Full Scan	280mm x 210mm (dependent upon timing signal)
OPERATING	Temperature	32–104°F (0–40°C)
CONDITIONS	Humidity	10–90% (no condensing)
DIMENSIONS	Physical (mm)	360mm x 362mm x 384mm
(W x H x D)	Physical (in.)	14.2" × 14.3" × 15.1"
WEIGHT	Net	24.6 lb. (11.2 kg)
	Gross	28.6 lb. (13.0 kg)
REGULATIONS		ENERGY STAR [®] , BSMI, PSB, UL /cUL, FCC-B, DHHS, ICES-B,
		Tuv-S, MPR II
POWER MANAGEMENT		Meets MPR II and ENERGY STAR® standards
PACKAGE CONTENTS		CRT monitor, video cable (attached), power cable,
		Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty on CRT, parts and labor



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967• Fax (909) 839-7922• SalesInfo@ViewSonic.com • ViewSonic.com *Excludes major U.S. holidays. **Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2005 ViewSonic Corporation. All rights reserved. [12574-00B-08/05] E55-4/E55B-4

For more product information, visit us on the web at ViewSonic.com

Downloaded from www.Manualslib.com manuals search engine